

meguinfo

Art.-No.: 3600.000 Stand: 04.08

megol Kühlerfrostschutz

megol Kühlerfrostschutz is a high quality ethylene glycol-based anti-freeze, which must be diluted with water before use. It contains specific additives that protect all metallic parts, including aluminium alloys, of the cooling system of petrol and diesel engines from corrosion and rust, prevent the formation of foam and guarantee optimal protection from cavitation. In addition it does not harm the coating, hose and seal materials currently in use. Petrogel anti-freeze S contains no nitrite, phosphate or amine and is compatible with all conventional quality anti-freeze products. Tap water of drinking quality is ideal for using with it. Petrogel anti-freeze S meets the conditions of the automotive industry and is suitable for use in all licensed motor vehicles in Europe.

Characteristic data				Approx.
Density at 20°C	DIN 51757	g/cm³	Q,Y	
Viscosity at 20°C	DIN 51562	mm²/s	Y	
Refraction index	DIN 51423			
Flash point	DIN 51758	°C		
Boiling point	ASTM D 1120	°C		
Water content	DIN 51777	%		
Ash content	ASTM D 1119	%		
Reserve alkalinity, n/10 HCL	ASTM D 1121	ml		
pH value Pure product	ASTM D 1287			
Ice flocculation points 50% in water 33% in water	ASTM D 1177	°C °C		
Congealing points 50% in water 33% in water	DIN 51583	°C		

Shanghai Jichuan Trading Co.,Ltd.Add: No 1201, Yinhai Building, Caoxi Road,
Xuhui District, ShanghaiTel: (86) 021-6482009924h Hotline: 15900706965Fax: (86) 021-64513829Website: www.pingyiao.comE-mail: info@jichuan.sh.cn

Approx. values