

Shanghai PingYiao Trading CO., Ltd.

IBERCUT 12 AM

Translation of the original Spanish. In case of a discrepancy, the Spanish original prevails

Description and Recommendations

A pure, very liquid oil formulated with natural paraffin refined base oils and special additives that facilitate steel straightening. It is a good idea to clean the tanks well before using the new product.

Properties

Provides excellent protection to tools and prolongs their useful life. Its excellent oiliness improves the finish of parts and avoids chip soldering and the seizing up of tools. Contains special additives that minimise the appearance of "oil mist".

Quality level

ISO 6743/7 category ISO-L-MHF

Technical characteristics

| | UNITS | METHOD | VALUE |
|--------------------------------|----------|---------------|--------------|
| Appearance | | , | Straw yellow |
| Colour | g/ml | ASTM D 1500 | <1,5 |
| Density at 15°C | cSt | ASTM D 4052 | 0,850 |
| Viscosity at 40°C | cSt | ASTM D 445 | 11 |
| Viscosity at 100°C | - | ASTM D 445 | 2,8 |
| Viscosity rate | mg KOH/g | ASTM D 2270 | 110 |
| Acidity index | ℃ | ASTM D 664 | 0.1 |
| Pour point | °C | ASTM D 97 | -22 |
| Ignition point | % | ASTM D 92 | 175 |
| Noack volatility, 1hr 200 °C | | CEC L-40-A-93 | <15 |
| Four ball machine test | kg | | |
| - Soldering load, IP239 | kg | | 200 |
| - Last load without seizing up | | | 400 |
| - Load/wear index | | | 43.2 |

Overview

Bulk.

Hazard identification

This product is not classified as toxic or hazardous under current legislation.

Handling

Shanghai Ping Yiao Trading CO., Ltd. Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Minimum precautions should be taken to avoid prolonged contact with the skin. The use of gloves, visors or glasses is recommended to avoid splashes.

Health and safety risks.

Inhalation: As this product has low volatility, the risk of inhalation is minimal. Ingestion: Do not make an affected person vomit. Supply water. Get medical help. Contact with the skin: Wash thoroughly with soap and water. Eyes: Wash thoroughly with water. General measures: Get medical help.

Fire-fighting measures

No special measures required.Extinction: Foams, dry chemicals, CO2, water spray. Do not apply a jet of water directly, as it could spread the product.

Environmental precautions

Danger of physical pollution if spilt (water, coastlines, soil, etc.) due to its floatability and oily consistency that may harm flora and fauna on contact. Prevent the material from entering thewater supply. Decontamination and cleaning: Treat as an accidental oil spillage. Avoid dispersion using mechanical barriers and remove with physical or chemical elements.

Shanghai Ping Yiao Trading CO., Ltd. Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com