



Shanghai PingYiao Trading CO., Ltd.

CIRCULACIÓN

Description

These oils are made from carefully selected and specially treated paraffin bases, which give the finished products high viscosity, good resistance to oxidation and excellent de-emulsifying qualities. They are prepared in viscosity grades traditionally used in the lubrication of bearings of the rolling mills.

Recommended uses

These are typical oils to lubricate by circulation the bearings subjected to severe services, used in strip mills.

Because of their characteristics they are also for lubrication of industrial reducers not subjected to shocks or big loads, as well as for some compressor casings which require these viscosities and do not need antiwear oils. They are also suitable for low-speed smooth bearings of a wide diameter, with drop-feed oiling, bath oiling or ring oiling.

Characteristics

High viscosity index.

Low pour point.

Elevated stability.

Low carbon residue.

Very good water separation.

Good anti-rust properties.

Quality Level

ISO 6743/2 - FC

DIN 51517 part 2-CL

Technical data

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

	UNITS	METHOD	VALUE	VALUE	VALUE	VALUE	VALUE
Type			220	320	390	460	680
ISO Grade			220	320	(390)	460	680
Viscosity at 40°C	cSt	ASTM D 445	230	320	390	460	680
Viscosity Index		ASTM D 2270	95	95	95	95	95
Flash Point	°C	ASTM D 92	235	240	250	265	265
Pour point	°C	ASTM D 97	-10	-10	-10	-10	-10

Available in

Bulk and Drums of 185 kg all grades

Hazard identification

This product is not classified as toxic or hazardous under current legislation.

Handling

Certain minimum precautions to avoid prolonged contact with the skin should be taken when handling. The use of gloves, visors or masks is recommended in order to avoid splashes.

Health and Safety Hazards

Inhalation: Minimum risk of inhalation as it is a non-volatile product.

Ingestion: Do not provoke vomiting. Drink water. Seek medical assistance.

Contact with Skin: Wash with abundant water and soap.

Eyes: Wash with abundant water.

General measures: Seek medical assistance.

Fire fighting measures

No special measures are required.

Fire control: Foams, dry chemicals, CO₂, water spray. Do not apply water jet directly as this may cause the product to spread.

Environmental Precautions

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Danger of physical contamination in the case of spillage (water flows, coastal areas, the ground, etc.) due to its floating capacity and oily consistency which may cause damage to fauna and flora with which it comes into contact. Avoid its penetration into water containers or outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Avoid spreading by using mechanical barriers and eliminate using both physical and chemical means.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com