

MULTIUSO EXTRA SAE30 Y SAE 40**Description**

Repsol Multiuso Extra Oils are made from carefully selected base stocks that have been treated in order to greatly improve their natural adhesiveness.

Recommended uses

General lubricating oils well suited for lost-applications. Particularly suitable for use on chain saws.

Properties

Marked stickiness.

High viscosity index.

Good corrosion protection.

Quality level

ISO 6743/1 – AN

DIN 51501 L-AN

Technical Characteristics

	UNIT	METHOD	VALUE	VALUE
ISO VG Grade			30	40
Viscosity, 40°C	cSt	ASTM D 445	100	150
Viscosity, 100°C	cSt	ASTM D 445	11	14.5
Viscosity Index		ASTM D 2270	95	95
Flash Point	°C	ASTM D 92	210	220
Pour Point	°C	ASTM D 97	-15	-10
Cooper corrosion		ASTM D 130	1a	1a
Rust, method A		ASTM D 665	Pass	Pass

Available in

Bulk. 185 and 45 Kg. drums. 5 litre metal cans.

Hazard Identification

This product is not classified as toxic or hazardous under current legislation.

Handling

Certain minimum precautions to avoid prolonged contact with the skin should be taken when handling. The use of gloves, visors or masks is recommended in order to avoid splashes.

Health and safety hazards

Inhalation: Minimum risk of inhalation as it is a non-volatile product.

Ingestion: Does not provoke vomiting. Drink water. Seek medical assistance.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

Contact with Skin: Wash with abundant water and soap.

Eyes: Wash with abundant water.

General measures: Seek medical assistance.

Fire fighting measure

No special measures are required.

Fire control: Foams, dry chemicals, CO₂, water spray. Do not apply water jet directly as this may cause the product to spread.

Environmental precautions

Danger of physical contamination in the case of spillage (water flows, coastal areas, the ground, etc.) due to its floating capacity and oily consistency which may cause damage to fauna and flora with which it comes into contact. Avoid its penetration into water containers or outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Avoid spreading by using mechanical barriers and eliminate using both physical and chemical means.