



Shanghai PingYiao Trading CO., Ltd.

V-W

Description

These are pure mineral oils obtained from paraffin crude and subjected to a rigorous refining process. They have excellent oiliness and anti-aging properties. Such characteristics make these oils suitable for all types of applications not having any special requirements, including lost lubrication systems.

Recommended uses

The Repsol V-W range of products is recommended for all types of mechanisms using a lost lubrication system, that is by drip feed or similar, and general all those mechanism requiring lubricants with only a minimum of special characteristics.

Properties

High quality uninhibited oils.

Good oiliness properties.

High viscosity index.

Excellent Lubricity

Low pour point.

Quality level

DIN 51501 L-AN

ISO 6743/1 L-AN

Technical Characteristics

	UNIT S	METHO D	V			W		
			VALU E	VALU E	VALU E	VALU E	VALUE	VALU E
ISO VD grade			15	46	68	100	(130)	150
Viscosity, 40°C	cSt	ASTM D 445	15	46	68	100	128	150
Viscosity, 100°C	cSt	ASTM D 445	3.4	6.7	8.5	11.2	13.2	14.6
Viscosity Index		ASTM D 2270	95	95	95	95	95	95
Pour Point	°C	ASTM D 97	-27	-24	-24	-24	-21	-18
Flash Point	°C	ASTM D 92	170	200	210	220	225	230

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Rust, Method A		ASTM D 665	Pass	Pass	Pass	Pass	Pass	Pass
Kopper corrosion, 3h, 100° C	mg KOH/g	ASTM D 130	1b	1b	1b	1b	1b	1b

Available in

ISO 15: 180 Kgs. Drums

ISO 46, 68, 130 and 150: 185 Kgs. Drums.

ISO 100: 875 kgs. Container and 185 Kgs. Drums.

Hazard Identification

This product is not classified as toxic or hazardous under current legislation.

Handling

Certain minimum precautions to avoid prolonged contact with the skin should be taken when handling. The use of gloves, visors or masks is recommended in order to avoid splashes.

Health and safety hazards

Inhalation: Minimum risk of inhalation as it is a non-volatile product.

Ingestion: Does not provoke vomiting. Drink water. Seek medical assistance.

Contact with Skin: Wash with abundant water and soap.

Eyes: Wash with abundant water.

General measures: Seek medical assistance.

Fire fighting measure

No special measures are required.

Fire control: Foams, dry chemicals, CO₂, water spray. Do not apply water jet directly as this may cause the product to spread.

Environmental precautions

Danger of physical contamination in the case of spillage (water flows, coastal areas, the ground, etc.) due to its floating capacity and oily consistency which may cause damage

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

to fauna and flora with which it comes into contact. Avoid its penetration into water containers or outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Avoid spreading by using mechanical barriers and eliminate using both physical and chemical means.

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoyi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com