

**REPSOL****Shanghai PingYiao Trading CO., Ltd.****REPSOL**
INDUSTRIAL*TELEX W*

Description and Recommendations

A high quality multigrade oil made from paraffinic base stocks which are treated with special solvents during the refining process which give it better oxidation protection and an increased service life.

Selected additives are used to give them a variety of properties including outstanding anti-wear characteristics. In general this is a hydraulic fluid for use on road machinery, however, its special additives also make it suitable for use on some transmissions of the same type of machinery.

Properties

High anti-wear protection.

Low pour point

Good anti-oxidation properties.

High viscosity index.

Good foam prevention characteristics.

High detergent-dispersant performance.

Good aging resistance.

Quality Level

DIN 51524/2 HLP (except demulsion)

MAN H-LPD

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoyi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

AFNOR NFE 48603 HM (except demulsion) CATERPILLAR TO-2

GM Allison C-4

Technical Characteristics

	UNIT	METHOD	VALUE
SAE Grade			10w/20
Viscosity, 100° C	cSt	ASTM D 445	7,0
Viscosity, 40° C	cSt	ASTM D 445	44
Viscosity, -20° C	cP	ASTM D 5293	3500 max.
Viscosity Index		ASTM D 2270	115
Flash Point , C/O	° C	ASTM D 92	210
Pour Point	° C	ASTM D 97	-33
Copper corrosion		ASTM D 130	1
T.B.N.	mgKOH/g	ASTM D 2896	10
Sulphated Ash	%	ASTM D 874	1,3

Available in

875 Kg. containers.

185 and 45 Kg. drums.

Hazard Identification

This product is not classified as toxic or hazardous under current legislation.

Handling

Certain minimum precautions to avoid prolonged contact with the skin should be taken when handling. The use of gloves, visors or masks is recommended in order to avoid splashes.

Health and safety hazards

Inhalation: Minimum risk of inhalation as it is a non-volatile product.

Ingestion: Does not provoke vomiting. Drink water. Seek medical assistance.

Contact with Skin: Wash with abundant water and soap.

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Eyes: Wash with abundant water.

General measures: Seek medical assistance.

Fire fighting measure

No special measures are required.

Fire control: Foams, dry chemicals, CO₂, water spray. Do not apply water jet directly as this may cause the product to spread.

Environmental precautions

Danger of physical contamination in the case of spillage (water flows, coastal areas, the ground, etc.) due to its floating capacity and oily consistency which may cause damage to fauna and flora with which it comes into contact. Avoid its penetration into water containers or outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Avoid spreading by using mechanical barriers and eliminate using both physical and chemical means.

Unless otherwise specified, the values cited in technical characteristics should be considered as typical.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com