

# Rhenus Nor SSK 30

## Chain Lubricant

### Description

**Rhenus Nor SSK 30** is chain oil based on mineral oil without graphite.

### Application and Properties

**Rhenus Nor SSK 30** is recommended for immersion lubrication and preservation for all kind of Fleyer- and roller chains.

**Rhenus Nor SSK 30** is suitable for different thickness within a temperature range of 35°C to 100°C.

**Rhenus Nor SSK 30** is stable in its consistent structure and can be applied up to -40°C.

**Rhenus Nor SSK 30** is free of barium, PTFE and silicone.

**Rhenus Nor SSK 30** is registered by NSF (National Sanitary Foundation) category code H2.



#### Advantages:

- variable coating
- variable temperatures
- simple to handle
- good anti-corrosion properties
- good adhesiveness
- high antiwear-properties

### Technical Data

Operating temperature*		-40 to 130 °C
Flashpoint	ISO 2529	> 210°C
Melting point		Approx. 30°C
type of base oil		Mineral Oil
Water hazard class WGK (Self-assessment)		WGK 2
viscosity at 40°C 50°C 70°C 100°C	DIN 51 562	177,8 mm²/s 106,2 mm²/s 45,3 mm²/s 17,4 mm²/S
Corrosion protection with NaCl	DIN 50 021 - SS	120 h

\*The temperature specifications are guidelines, oriented towards the lubricant composition, the application purpose and the application technique. Lubricants change their consistence according to the appearance of the mechanical-dynamic demands and viscosity, respectively. These changes of the product characteristics can influence the functioning of components.

Subject to modification of the technical data. Please refer to the material safety data sheet for additional information or contact our application engineers.

### Edition

01/05 so

Shanghai Ping Yiao Trading Co., Ltd.

TEL: 86 21 6470 5533 24H:15900706965

FAX: 86 21 6482 0538 <http://www.pingyiao.com> Email:[info@pingyiao.com](mailto:info@pingyiao.com)

Rhenus is certified according to ISO/TS 16949, DIN EN ISO 9001, DIN EN ISO 14001 and OHSAS 18001.