



SHANGHAI PING YIAO TRADING CO.,LTD.
Tel: 86-21-64705533
Fax: 86-21-64820538
24H: 86-15900706965
Website: www.pingyiao.com
E-mail: info@pingyiao.com

Special mould-cleaner

Removes effectively polymer residues – resins – oil deposits

S.F.R. penetrates and dissolves

- polyurethane, polyacrylate, polyamide, polystyrene
- cellulose acetate
- epoxide resins
- oil deposits, oil-carbon
- and many others

from metallic surfaces.

S.F.R. is used to clean moulds and tools at injection moulding machines, flat film extrusion lines, blown film extrusion lines, spinning plants and extrusion plants.

S.F.R. does not attack metals.

Technical data:

Density at 20°C:	1.01 (g/ml)	Odour:	sweetish
Vapour pressure:	120 hPa	Combustibility:	combustible
Evaporation:	S.F.R. does not evaporate under normal circumstances.		
Material attack:	S.F.R. attacks plastics, elastomers, paints and lacquers.		

Application: Please spray RIVOLTA S.F.R. onto the parts which are to be cleaned. After an exposure time depending on the coating thickness please remove the cleaner by wiping it off.

For the complete removal e.g. in cavities we recommend to use our rapid evaporating cleaner spray A.C.S. 3 in addition.