

**Electro-safety cleaner** 



SHANGHAI PING YIAO TRADING CO.,LTD. Tel: 86-21-64705533 Fax: 86-21-64820538 24H: 86-15900706965 Website: www.pingyiao.com E-mail: info@pingyiao.com

Top-quality safety cleaner for all electrical installations, equipments and engines – based on pure basic materials - evaporation without any residues - almost odourless

product is free of halogenated nd carcinogenic compounds. The per does not create any risks for the
kinds of electrical installations and transformers, rectifiers, electric hgears and devices, electrical nd hoisting equipment, insulators, ndition-systems etc.

**RIVOLTA S.L.X. Super** can be used for many cleaning-procedures like immersion, washing, brushing or spraying. In addition it may be applied with an airless or an electric spray gun with a needle-jet nozzle.

Colour: clear, colourless		Odour: almost odourless	
Technical data	Unit of measurement	Norm	S.L.X. Super
Density (20°C)	g/ml	DIN 51757	0.762
Flashpoint	°C	DIN EN ISO 2719	>+61°C
<b>Evaporation rate</b>	ETHER = 1	DIN 53170	100
Dielectric strength	V/cm	DIN 57370	240,000

**RIVOLTA S.L.X. Super** evaporates without residues. In connection with the high dielectric strength, S.L.X. Super allows a simple cleaning of all electrical installations and equipments without dismantling. S.L.X. Super is highly effective in removing of resistant contaminations.

**RIVOLTA S.L.X. Super** is insoluble in water. Does not create stable emulsions with water. Separates quickly.

This text contains facts and statements and is determined with our best knowledge and will be checked continuously. These statements are depending - among other reasons - on experiences gained in the industry. We only pass them on without liability. Before using our products you should test the applicability and you should convince yourself about the satisfactory performance. Our application examples and suggestions should not request to violate patent rights.