



UCON Fluids&Lubricants Shanghai Ping Yiao Trading Co.,Ltd

UCON Coating Fluids

UCON™ LB Series base fluids can be compounded with selected rust and oxidation inhibitors to serve as lubricating and protective coatings for hydraulic brake parts and similar equipment before and during assembly. They are compatible with DOT 3 brake fluids but not silicone-based fluids. UCON coating fluids have no adverse effect on braking system elastomers and provide lubrication during the assembly of braking parts.

The table below lists the typical viscosity[†] to help you select which base stock will meet your needs.

Product	Description	Viscosity 37.8°C (100°F) cSt
UCON Coating Fluid LB-165-Y24	A rust-preventive fluid used to coat metal parts.	35.6 – 41.0
UCON Coating Fluid LB-285-Y3	A rust-preventive fluid used to coat metal parts.	61.5 – 68.0
UCON Coating Fluid LB-550-XY26	A rust-preventive fluid used to coat metal parts.	114 – 145
UCON Coating Fluid LB-1145-Y23	A rust-preventive fluid used to coat metal parts.	250 – 285
UCON Coating Fluid LB-1145-Y24	A rust-preventive fluid used to coat metal parts.	237 – 275
UCON Coating Fluid LB-1145-Y27	A rust-preventive fluid used to coat metal parts.	237 – 275
UCON Coating Fluid LB-1200-XY23	A rust-preventive fluid used to coat metal parts.	250 – 289

[†] Typical properties, not to be construed as specifications.

Shanghai Ping Yiao Trading Co.,Ltd
Tel: 86 21-64705533
Fax: 86 21-64820538
24H: 86 15900706965

E-mail: info@ pingyiao.com
Website: www.pingyiao.com