



UCON Fluids&Lubricants Shanghai Ping Yiao Trading Co., Ltd.

UCON Compressor Lubricant R-1

Product

Description

UCON™ Compressor Lubricant R-1 is a water-soluble polyalkylene glycol lubricant specially formulated for use in high-pressure reciprocating compressors in natural gas service.

UCON Compressor Lubricant R-1 has found particular success in compressors used for the high-pressure (>3000 psig) injection of surplus gas back into oil field formations. This reinjection both conserves natural gas resources and serves to maintain pressure in the oil-producing formation. UCON Compressor Lubricant R-1 has also been used successfully in high-pressure injection of nitrogen.

Product Features

- Low solubility with hydrocarbons
- Good lubricity for cylinder lubrication
- Nonplugging in oil field formations

Advantages

Because of its chemical composition, UCON Compressor Lubricant R-1 is water-soluble and has very low solubility with hydrocarbons, unlike a petroleum-based lubricant.

This is very important because:

- Natural gas dissolved into a lubricant has the effect of reducing lubricant viscosity, which could result in cylinder scoring and high packing wear rates. Compensating by using higher-viscosity lubricant results in other problems, especially at low temperatures.
- Lubricant dissolved in natural gas will actually be carried away, depleting the lubricating film in the cylinder. This leads to high use-rates or lubrication failures.
- UCON Compressor Lubricant R-1 carried over into the formation will not form sludges, which plug the oil field formation.

UCON lubricants of this type have been used over 25 years in similar applications. A UCON lubricant was chosen as the compressor lubricant to minimize carry-over downwell for underground natural gas storage fields because of its low hydrocarbon solubility. UCON lubricants have also been used in high-pressure (5000 psig) reciprocating compressor in nitrogen service with excellent results.

In addition to the unique properties necessary for this type of application, all UCON lubricants exhibit high viscosity indices, good film strength, excellent thermal stability and resistance to sludge formation.

Shanghai Ping Yiao Trading Co., Ltd.

Tel: 86 21-64705533

Fax: 86 21-64820538

24H: 86 15900706965

Email: info@pingyiao.com

Website: www.pingyiao.com



UCON Fluids&Lubricants Shanghai Ping Yiao Trading Co., Ltd.

Typical Physical Properties

Viscosity	
(cSt at 40 °C)	195
(cSt at 100 °C)	35.1
(SUS at 100 °F)	985
Viscosity Index	229
Pour Point, °C(°F)	-43(-45)
Flash Point	
Cleveland Open Cup, ASTM D 92, °C(°F)	304(580)
Pensky-Martens Closed Cup, ASTM D 93, °C (°F)	240(465)
Turbine Oil Rust Test, ASTM D 665 A	Pass
Copper Strip Corrosion Test	1a
FZG Extreme Pressure test, Stages Passed	12
Coefficient of Expansion, at 55°C	0.00079 per °C
Density, lb/gal, 20°C	8.75
Specific Gravity, 20/20°C (68/68°F)	1.053

Case Study 1: High-Pressure Reciprocating Compressor for Natural Gas Reinjection

Problem

A Wyoming producer uses five Ingersoll-Rand reciprocating compressors for reinjection of natural gas into the oil field formation. Using a petroleum-based lubricant, the compressor's piston rings and rod packings showed scoring and abnormally high wear rates.

Solution

UCON Compressor Lubricant R-1 successfully solved this problem, allowing production from this field to continue for several years.



UCON Fluids&Lubricants

Shanghai Ping Yiao Trading Co., Ltd.

Details

Equipment: Ingersoll-Rand RDS 5 / " - stroke compressor, 710 rpm, 1200 hp, 3-cylinder, 3-stage (modified from 4-throw to 3-throw).

Output - 33 MMSCFD natural gas

Discharge Pressure - 6300 psia

Operating Conditions -

	Suction		Discharge	
	Temperature	Pressure	Temperature	Pressure
1 st Stage	50°F	750 psig	170-200°F	1800 psig
2 nd Stage	70°F	1800 psig	170-200°F	3000 psig
3 rd Stage	70°F	3000 psig	170-200°F	6300 psig

Composition - Piston Rings: Glass-filled Teflon, 1st and 2nd Stages, 90/10 lead/bronze, 3rd Stage

Cylinder Rods: Bronze, 1st and 2nd Stages

Packings: Teflon-bronze, 3rd Stage

Results

There has been no failure of lubricated parts, and a visual inspection showed no sign of abnormal wear.

Case Study 2: High-Pressure Reciprocating Compressor for Nitrogen Injection

Problem

Another secondary recovery project in Wyoming uses Ingersoll-Rand reciprocating compressors for injection of nitrogen into the oil field formation. Using a petroleum-based lubricant, the compressor's piston rings and rod packings showed scoring and abnormally high wear rates.

Solution

These two compressors were converted to UCON Compressor Lubricant R-1.



UCON Fluids&Lubricants

Shanghai Ping Yiao Trading Co., Ltd.

Details

Equipment: Ingersoll-Rand HHE 16" - stroke compressor, 327 rpm, 6300 hp, 4-cylinder.

Output - 33 MMSCFD nitrogen

Discharge Pressure - 6000 psia

Operating Conditions -

	Suction		Discharge	
	Temperature	Pressure	Temperature	Pressure
1 st Stage	60°	110 psig	230°F	300 psig
2 nd Stage	60°	300 psig	240°F	860 psig
3 rd Stage	60°	860 psig	240°F	2275 psig
4 th Stage	60°	2275 psig	240°F	6000 psig

Composition - Piston Rings: Thermoplastic and 90/10 lead/bronze

Rod Packings: Teflon-bronze

Results

After a three-month trial of UCON Compressor Lubricant R-1 on the HHE compressor, at this location. No signs of abnormal wear were detected. A second compressor of similar design was then converted to UCON Compressor Lubricant R-1.

Product Stewardship

Dow encourages its customers and potential users to review their applications from the standpoint of human health and environmental aspects. To help ensure that Dow products are not used in ways for which they are not intended or tested, Dow personnel will assist customers in dealing with environmental and product safety considerations. Dow literature, including Material Safety Data Sheets, should be consulted prior to the use.